







NOTE

1. PLEASE USE THE NON-RADIUS SIDE FOR THE PANEL HOOKING AREA.
2. APPLICABLE PANEL THICKENING IS 1.6 TO 1.0mm.
(A SLIGHT DEVIATION WILL OCCUR FOR THE THICKNESS EXCEPT FOR 1.6 AND 1.2mm.)
3. LENGTH OF MATING WITH 'DF11-DC-2C' IS 15.3mm.
4. THE WALL IN CENTER DOESN'T EXIST FOR 4 AND 6 CONTACTS.

				1	PORYAMIDE	UL94V-0(BLACK)		
NO.	MATERIAL	FINISH , REMARKS		NO.	MATERIAL	FINISH , REMARKS		
UNITS mm  HIROSE ELECTRIC CO., LTD.		SCALE	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
		5 : 1	3	DIS-H-004178		YK. NAKATSU	TS. FUKUSHIMA	09. 09. 14
		APPROVED : KJ. KATAYOSE		05. 01. 05	DRAWING NO.	EDC3-081880-01		
		CHECKED : TY. OMA		05. 01. 05	PART NO.	DF11- * DEP-2C		
		DESIGNED : IO. DENPOUYA		05. 01. 05	CODE NO.	CL543-		
DRAWN : IO. DENPOUYA		05. 01. 05					 	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Hirose Electric:](#)

[DF11-12DEP-2C](#)