







LOC	DIST	REVISIONS					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
A1	2		B5	REVISED PER ECR-17-002907	23OCT2017	JB	DZ

- MATES WITH APPROPRIATE UNIVERSAL MATE-N-LOK PLUG
- RECOMMENDED PANEL THICKNESS 0.76 - 2.29 mm
- PANEL MUST BE PUNCHED SO THAT THE HOUSING ENTERS THE PANEL IN THE SAME DIRECTION AS THE PUNCH
- CIRCUIT NUMBER 1 LOCATION
- DIMENSION INDICATED AS MOLDED. ADDITIONAL GROWTH DUE TO SUBSEQUENT MOISTURE ABSORPTION MAY OCCUR
- UNDERWRITERS RECOGNIZED COMPONENT LOGO AND CSA CERTIFICATION LOGO TO BE LOCATED ONCE EACH ON SIDE OF HOUSING
- MATERIAL CORRESPONDING TO THE REQUIREMENTS OF IEC 60335 (INCL. GLOW WIRE TEST 750°C, WITHOUT FLAME)
- OPTIONAL FOR KEYING HOUSING IN PANEL
- PRELIMINARY PART NOT RELEASED FOR PRODUCTION

	1-1703062-2	A	PA66 UL94 V0 (GW T 750 °C)	NATURAL
	1-1703062-1	1	PA6 UL94 V0	NATURAL
	1703062-4	A	PA6 UL94 V2 GW T 750 °C	BLACK
	1703062-3	A	PA6 UL94 V2 GW T 750 °C	RED
	1703062-2	A	PA6 UL94 V2 GW T 750 °C	BLUE
	1703062-1	A	PA6 UL94 V2 GW T 750 °C	NATURAL
REMARK	PN	REV	MATERIAL	COLOUR

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN MAHNKE, B. 16APR2004 CHK ZITZ, A. 26APR2004 APVD BLEICHER, M. 27APR2004	TE Connectivity		
DIMENSIONS: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED:	NAME CAP 2 CIRCUIT UNIVERSAL MATE-N-LOK		
0 PLC ± 1 PLC ± 2 PLC ±0.13 3 PLC ± 4 PLC ±		±°	SIZE CAGE CODE DRAWING NO RESTRICTED TO		
MATERIAL 7 PA 6		FINISH	A2 00779 C-1703062		
CUSTOMER DRAWING		SCALE 4:1	SHEET 1 OF 1 REV B5		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1703062-1](#)